

G₃U

License Free
Walkie - Talkie
UHF Analog Handheld
ETA-SD-20191106922

WPC Approved, Govt Order No.-1047{E}
Dated 18 Oct., 2018

- Unique & Light
- Time Out Timer
- Easy to Operate
- Attractive Design
- CTCSS / DCS Function
- Busy Channel Lock Out
- Protection Against High VSWR



G3U portable two-way radio has superior audio quality, outstanding coverage, long-lasting battery life and more connects your workforce efficiently-and has the flexibility to grow with your business. **G3U** portables provide the features and performance needed for a wide range of workplaces. Whatever your needs, **G3U** provides a simple, reliable, cost-effective communication solution to help work crews connect, coordinate and collaborate to get the job done right. Improve the efficiency of your operation with easy-to-use voice communication.






G3U


License Free Walkie - Talkie UHF Analog Handheld

Specifications

G3U	
General	UHF
Frequency Range	446 - 446.2 MHz
No. of Channel	16 Channels
Capacity Battery Life	2600 mAh Li-Ion (Standard)
Operating Temperature	0°C to +55°C
Dimension: HXWXD	119 X 56 X 36mm
Weight (Net Weight)	155gm (Including Antenna & Battery)







	G3U Reciever		
		NARROW BAND	
ĺ	Sensitivity (12 dB SINAD)	0.2μV @12dB SINAD	
	Intermodulation EIA	Better than 60dB	
	Adjacent Channel Selection	65dB or Better	
	Spurious Response	Better than 65dB	
	Audio Response	+1 ~ -3dB	
	Audio Distortion	≥3%	
	Audio Power Output	500mW	
		Transmitter	
	RF Power	0.5W (ERP)	
	Adiacont Channal Bawar	B .: .: .:	

Transmitter		
RF Power	0.5W (ERP)	
Adjacent Channel Power	Better than -60dB	
Modulation Limiting	+≤5Khz@25Khz	
FM Hum & Noise	-40dB	
Conducted/ Radiated Emission	-36Bm<1GHz, -30dBm>1GHz	
Audio Response	+1 ~ -3dB	
Audio Distortion	≤ 3%	



Marketed: Dealer/Distributor